



Wrap Around Labels Self-Laminating



Product Overview:

The Sumitag® self-laminating wrap around label is a clear-matte flexible vinyl film with a permanent acrylic pressure sensitive adhesive backed with a bleached Kraft release liner. The printable area is constructed with a surface that is smooth for thermal transfer printing. Resin ribbons are recommended for optimal durability. The triple notch design offers the ultimate in printer flexibility for compact desk model thermal printers to capacity industrial printers.

Application, Storage & Service:

- Wire & Cable Identification
- RJ45 Cables, Fiber Optic Cables, Coax Cables
- Oil, Water and Solvent Resistant
- Service Temperature Range:
-40°F to +176°F (-40°C to +80°C)
- Minimum Application Temperature 50°F (10°C)
- Expected Exterior Life 2 Years
- Shelf life: 12 months of manufacture of product

Standards:

- UL-969 Marking Standards
- UL File #PGGU2.MH10170



3 locations to serve you

New England 800-346-3526

Mid- Atlantic 866-635-2660

Southeast US 800-899-8533

www.Nelcoproducts.com

www.Wiremarkersplus.com



Wrap Around Labels Self-Laminating

Recommended Printer & Ribbon:

Sumitag™ Printer	STP-300 SS
Ribbon	SM3 Black

Technical Specifications:

Property	Value	
Adhesion from	Average (oz/in)	Expected Range (oz/in mNM)
Stainless Steel	82.5	65-100
Acrylic	77.5	60-95
Glass	77.5	60-95
Expected Sheer (hours)	20	
Top Coat	3.5 mil (0.0889 mm)	
Film	Matte Flexible Film	
Adhesive	Acrylic 0.8-0.9 (0.02-0.023mm)	
Liner	3.1 mil (0.079mm) Densified Kraft	

Max Wire Cable Diameter	Width (MM) A	Height (MM) A	Print Area (MM) C	Roll Size	Part Number
3.15	12.7	19	9.10	5,000	SWA-127-190
5.00	12.7	23.8	8.30	10,000	SWA-127-238
8.00	12.7	38.1	12.7	10,000	SWA-127-381
7.58	20.3	36.5	12.7	10,000	SWA-203-365
7.58	25.4	38.1	12.7	5,000	SWA-254-381
12.16	25.4	57.2	19.0	5,000	SWA-254-572
22.22	25.4	95.3	25.4	5,000	SWA-254-953
28.37	25.4	190	38.1	2,500	SWA-254-190
19.64	48.3	80.7	19.0	1,000	SWA-483-810
36.56	47.6	145	30.1	2,000	SWA-476-145
7.00	50.8	34.9	12.7	2,500	SWA-508-349
12.00	50.8	57.1	19.1	1,000	SWA-508-571
22.21	50.8	95.2	25.4	1,000	SWA-508-952
35.61	50.8	150.0	38.10	2,000	SWA-508-150